


Resistant

co-extruded massive deck

Status May 2019



RESISTANT



Resistant in every way

Enjoy our new, co-extruded, especially sturdy and low on maintenance solid patio deck that you neither have to paint nor oil. The patio deck's core is made up of a composite material, a combination of 70 % domestic wood and an environmentally-friendly polymere. In an innovative production process this core is covered with a layer of polymere that protects it all over. This protective cover makes the surface water repellant and guarantees stain resistance. Because it is very UV resistant the colours will not change temporarily. This resistant patio deck is extremely suitable for surfaces partially covered by a roof.

Intensive colours, natural grain

Resistant is available in three new, intensive colours. Choose between the warm shade sand, vibrant umbra and modern gravel. Its surface, which is created to look like exotic hardwoods, is stamped on one side and brushed. Laying it on one side with a small gap width of ca. 5 mm creates an especially uniform and elegant look.

Characteristics

water repellant
stain resistant
especially low on maintenance
excellent UV resistance

Simple laying

The special laying aid that you receive on purchasing the new patio deck is to enable rational and even laying creating a small, elegant gap width of only ca. 5 mm. Depending on the locational situation you will need ca. 2.5 to 3 metres of base profile and ca. 16 stainless steel brackets with screws to lay one square metre. With this deck you cannot use a joint profile tube and mounting clip, you have to use our universal accessories to lay the decks. You can find laying films on patio construction and current information on our products on our website!

Good planning is everything

Use our patio planner to plan your favourite spot with our deck RESISTANT. Choose between different laying shapes and directions and use the practical material list to implement your plans. You are also welcome to ask for consultation directly from one of our partner retailers.

Format	width ca. 138 mm, height ca. 23 mm
Surface	stamped on one side, slightly brushed
Standard lengths	ca. 5 m / ca. 6 m
Special lengths	none
Requirements	1 sqm consists of ca. 7 m decks
Weight	ca. 3.7 kg / m

Narrow gap measurement of only 5 millimetres



NATUR inFORM GmbH

Flurstraße 7

D-96257 Redwitz a. d. Rodach

T +49 (0) 9574 65473 - 0

F +49 (0) 9574 65473 - 20

info@naturinform.com

www.naturinform.de



Prüfung Rutschhemmung **DIE RESISTENTE**

R12

5/2019

Bewertung nach DIN 51130
TÜV Rheinland/LGA



This brochure was created carefully for you and is constantly being developed further. Please find the current and valid version at www.naturinform.com. Printed colours can vary.
Status: May 2019